

## General Safety Information

### ⚠ WARNING

- Obtain and read the service instructions carefully prior to installing the parts. Loose, worn, or damaged parts may cause injury to the rider. We strongly recommend only using genuine Shimano replacement parts.
- Read these Technical Service Instructions carefully, and keep them in a safe place for later reference.

### Note

- Operation of the levers related to gear shifting should be made only when the front chainwheel is turning.
- For smooth operation, use the specified outer casing and the bottom bracket cable guide.
- Grease the inner cable and the inside of the outer casing before use to ensure that they slide properly.
- Use a frame with internal cable routing is strongly discouraged as it has tendencies to impair the SIS shifting function due to its high cable resistance.
- A special grease is used for the gear shifting cable (SIS-SP41). Do not use DURA-ACE grease or other types of grease, otherwise they may cause deterioration in gear shifting performance.
- The cycle computers shown in the table below are compatible.

Meter unit	SC-6502
Bracket sensor unit	SM-SC70

- Read the service instructions for the cycle computer also.
- Please refer to the Service Instructions for the ST-7801 / ST-7803 for details on installation and maintenance.
- Be sure to read these service instructions in conjunction with the service instructions for the FD-7803 before use.
- Parts are not guaranteed against natural wear or deterioration resulting from normal use.
- For maximum performance we highly recommend Shimano lubricants and maintenance products.
- For any questions regarding methods of installation, adjustment, maintenance or operation, please contact a professional bicycle dealer.

## Technical Service Instructions

SI-6K10A


# ST-7803

## Front DUAL CONTROL Lever

In order to realize the best performance, we recommend that the following combination be used.

Series	DURA-ACE
Shifting lever	ST-7803
Outer casing	SP41
Gears	30
Front derailleur	FD-7803
Front chainwheel	FC-7803
Rear derailleur	RD-7800 (GS Type)
Freehub	FH-7800
Cassette sprocket	CS-7800
Chain	CN-7801
Bottom bracket cable guide	SM-SP17

## Gear shifting operations



Lever (b) will also move when lever (a) is operated, but be careful not to apply pressure to lever (b). Similarly be careful not to press lever (a) when operating lever (b). Gears will not shift when both levers are pressed simultaneously.

Type of shifting	Lever operation
Smallest chaining → Intermediate chaining	<p>Lever (a)</p>
Intermediate chaining → Largest chaining	<p>Lever (a)</p>
Largest chaining → Intermediate chaining	<p>Lever (b)</p>
Intermediate chaining → Smallest chaining	<p>Lever (b)</p>

Operate lever (a) until gear shifting is complete.

Operate lever (b) until gear shifting is complete.

## Trimming (noise prevention mechanism) operation

Depending on the position of the chain after shifting, the chain may rub against the chain guide outer plate or the chain guide inner plate of the front derailleur, producing a characteristic noise. If this sort of thing happens, you can press lever (a) or lever (b) slightly to move the front derailleur a little way so that it does not touch the chain. This operation is called "trimming". Trimming can be carried out whether the chain is on the largest, intermediate or smallest chaining. If noise occurs when the chain is in one of the positions shown below, carry out trimming to eliminate the noise.

Chain position	Symptom	Lever operation	Trimming operation
Largest chaining	Chain contacts outer plate	<p>Lever (a)</p> <p>(Hits) Click</p>	<p>trimming operation</p> <p>Before trimming → After trimming</p> <p>Front derailleur movement</p>
Intermediate chaining	Chain contacts inner plate	<p>Lever (b)</p> <p>(Hits) Click</p>	<p>trimming operation</p> <p>Before trimming → After trimming</p> <p>Front derailleur movement</p>

# SHIMANO

SHIMANO AMERICAN CORPORATION  
One Holland Irvine, California 92618, U.S.A. Phone: +1-949-951-5003

These service instructions are printed on recycled paper.

SHIMANO EUROPE B.V.  
Industrieweg 24, 8071 CT Nunspeet, The Netherlands Phone: +31-341-272222

© Nov. 2004 by Shimano Inc. XBC SZK Printed in Japan

SHIMANO INC.  
3-77 Oimatsu-cho, Sakai, Osaka 590-8577, Japan